

# Signature Door Inc.

## Factory Finishing Process (Paint)

- » The entire unit is lightly sanded with 220 grit sandpaper to remove any silicone, oil, fingerprints, or other foreign materials that will prevent the primer and paint from properly adhering to the wood.
  - » Stain-blocking primer is sprayed on the unit. The unit then sits for an adequate amount of time to allow the primer to dry.
  - » Then two coats of paint are sprayed on the door. The entire unit is lightly sanded between coats with 240 grit sandpaper to remove any wood hairs that have risen during the application of the preliminary coat. In addition, the sanding enables the second layer of paint to better adhere to the previous layer.
- ∞ *Finished wood plugs (3/8" or 1/2") or wood strips (1" x 1/4") are available upon request to conceal any visible screw/nail heads due to the installation method utilized.*
- ∞ *A 1 ounce finish touch-up bottle of paint (with brush attached to the lid) is automatically included with a factory finished unit.*

## Maintenance Information

The top coat of paint on a finished unit must be maintained for the best protection of your wood entryway. Factory finished units are no exception. With direct exposure to sunlight or moisture, your unit may need to be recoated multiple times a year. A unit that is well protected from sunlight and moisture may only need to be recoated every one or two years. A unit should be closely inspected every 6 months to determine if the top coat is breaking down and needs a maintenance coat. The finish will start to look dull and worn in spots when it is time to recoat.

- ❖ If you would like to maintain the door using the exact product that was used to factory finish your door, this product is available for purchase by the public by contacting our Sales Team (sales@signaturedoor.com).
- ❖ You can also use any good quality exterior-grade latex paint to maintain the door. Please be aware that the color may not be an exact match to what is existing.

Regardless of which product you choose above, when you recoat your door, you will want to lightly sand the top layer of paint before applying the fresh coat. Lightly sanding will allow the fresh coat to adhere properly.

## Storage & Handling

To keep doors protected, use clean gloves and equipment when handling. Carry (do not drag) door units. Store on a level surface in a dry, well-ventilated building. If covered, allow for air circulation. Avoid stacking on end. If the doors are to be stored at the job site, the entire door unit must be sealed with an exterior-grade clear coat (with UV inhibitors) to regulate moisture absorption. Never subject doors to abnormal heat, dryness or humidity for prolonged periods. *Notice:* Wood doors should be conditioned to average prevailing relative humidity of the locality before hanging. Deliver doors to the job site in a clean truck and under cover in wet weather. Install only after all plaster, texture and/or concrete, etc. on the building site is dry.